

BUILDING WIRES SINGLE CORE, PVC INSULATED NON-SHEATHED



2

1


1. Single core conductor
2. PVC Insulation.

TYPE OF CABLE: H05V-U (UK: 6491X)
VOLTAGE: 300/500V
SPECIFICATION: ELOT 563 - HD 21.3 - BS: 6004

Applications

For internal wiring of switching boxes and other electrical appliances, for installation in closed conduits and tubes. Not for direct installation under plaster.

CONDUCTOR NOMINAL CROSS- SECTIONAL AREA	EXTERNAL DIAMETER (APPROX.)	NET WEIGHT (APPROX.)	MAXIMUM CONDUCTOR DC RESISTANCE AT 20° C	CONTINUOUS CURRENT RATING	VOLTAGE DROP	
					2 cables single phase AC or DC	3 or 4 cables three phase AC
mm ²	mm	Kg/Km	Ω/Km	A	mV / A/m	mV / A/m
0,5	2,3	9	36	3	87	75
0,75	2,5	11	24,5	6	59	51
1	2,7	14	18,1	10	44	38



2

1

1. Flexible conductor
2. PVC insulation

TYPE OF CABLE: H05V-K (UK: 2491X)
VOLTAGE: 300/500V
SPECIFICATION: ELOT 563 - HD 21.3 - BS 6004

Applications

Suitable for fixed protected installations in or on lighting fittings and inside appliances.

Colours

Identification of cores: Green/yellow, light blue, black, brown.

CONDUCTOR NOMINAL CROSS- SECTIONAL AREA	EXTERNAL DIAMETER (APPROX.)	NET WEIGHT (APPROX.)	MAXIMUM CONDUCTOR DC RESISTANCE AT 20° C	CONTINUOUS CURRENT RATING	VOLTAGE DROP	
					2 cables single phase AC or DC	3 or 4 cables three phase AC
mm ²	mm	Kg/Km	Ω/Km	A	mV / A/m	mV / A/m
0,5	2,5	9	39	3	94	81
0,75	2,7	11	26	6	63	54
1	2,8	14	19,5	10	47	41